

# Quick Reference Air Spring Chart



Refer to this chart to find the correct air spring for your application.



Description	Part Number	Max Ext. Height	Comp Height	Max Dia.	Design Height	Air Fitting Size (NPTF)	Top Fastener	Bottom Fastener	Mtg. Hole Centers
<b>Sleeves</b>									
Sleeve 4.0"	58482	7.0	2.4	4.6	4.0-6.0	1/8"	3/4" - 16	1/2" - 13	N/A
Sleeve 4.5***	58483	6.25	2.6	5.1	4.0-5.75	1/8"	3/4" - 16	1/2" - 13	N/A
Sleeve 4.0"	58287	8.75	3.1	4.6	5.5-7.5	1/8"	3/4" - 16	1/2" - 13	N/A
Sleeve 4.0***	58430	8.75	3.3	4.6	5.0-8.0	1/8"	3/4" - 16	1/2" - 13	N/A
Sleeve 4.5***	58387	6.75	2.6	5.1	4.0-6.0	1/8"	3/4" - 16	1/2" - 13	N/A
Sleeve 4.5"	58487	6.8	2.4	5.1	4.0-6.0	1/8"	3/4" - 16	1/2" - 13	N/A
Sleeve 4.5"	58987	7.75	3.1	5.1	4.5-7.0	1/8"	3/4" - 16	1/2" - 13	N/A
Sleeve 4.5"	58486	9.75	3.1	5.1	6.0-8.0	1/8"	3/4" - 16	1/2" - 13	N/A
Sleeve 4.0"	58586	9.91	3.1	4.6	6.0-8.5	1/8"	3/4" - 16	1/2" - 13	N/A
Sleeve 4.0"	58786	10.25	3.1	4.6	7.5-9.5	1/8"	3/4" - 16	1/2" - 13	N/A
Sleeve 4.5"	58571	10.25	3.1	5.1	6.5-8.5	1/8"	3/4" - 16	1/2" - 13	N/A
Sleeve 5.0"	58471	10.25	3.1	5.6	6.5-8.5	1/8"	3/4" - 16	1/2" - 13	N/A
<b>Bellows</b>									
Bellows 1B-5	58103	5.8	1.8	6.5	3.5-5.0	1/4"	3/8" - 16	3/8" - 16	1.75"
Bellows 1B-6	58407	7.1	1.9	7.0	4.0-6.0	1/8"	3/8" - 24	3/8" - 24	2.75"
Bellows 1B-6 Ultimate**	58740	7.0	2.7	7.0	4.0-6.0	1/8"	3/8" - 24	3/8" - 24	2.75"
Bellows 1B-8	58124	7.3	1.8	9.4	4.0-6.5	1/4"	3/8" - 16	3/8" - 16	2.75"
Bellows 2B-6, Reg.	58439	7.7	2.3	6.5	4.5-6.5	1/8"	3/8" - 24	3/8" - 24	2.75"
Bellows 2B-6, Reg. Ultimate**	58494	8.25	2.7	6.5	4.5-6.5	1/8"	3/8" - 24	3/8" - 24	2.75"
Bellows 2B-6, Ext.	58437	9.1	2.3	7.0	5.0-7.0	1/8"	3/8" - 24	3/8" - 24	2.75"
Bellows 2B-6, Ext. Ultimate**	58496	9.1	2.7	7.0	5.0-7.0	1/8"	3/8" - 24	3/8" - 24	2.75"
Bellows 2B-7, Ext.	58116	9.0	3.3	8.0	6.0-8.0	1/8"	3/8"-24	3/8"-24	2.75"
Bellows 2B-7, Ext. Ultimate**	58120	9.0	3.3	8.0	6.0-8.0	1/8"	3/8"-24	3/8"-24	2.75"
Bellows 2B-6, Ext. Pro Series**	58937	9.1	2.3	7	5.0-7.0	1/8"	3/8"-24	3/8"-24	2.75"
Bellows 2B-6, Reg. Pro Series**	58939	7.7	2.3	6.5	4.5-6.5	1/8"	3/8"-24	3/8"-24	2.75"
<b>Tapered Sleeve</b>									
1TS5.0"	58130	9.5"	4.25"	5.4"	6.5-8.5	1/4"	3/8"-24	3/8"-16	2.75"-Top Centered-Bottom

\*Replaces Firestone 255C

\*\*Has internal jounce bumper.

NOTE: When ordering replacement bellows for kit numbers 57125 and 57131, the mounting stud, P/N 17210, is not included.